


# Hydrogen Leak Sensor



## HLS-440P

### Fast and highly selective

The AppliedSensor HLS-440P Hydrogen Leak Sensor is an accurate, fast-responding sensor designed for installation in harsh environments such as fuel cell exhausts, for example. The sensor will measure hydrogen in the range of 0-10% in air or nitrogen.

### Low power and flexible packaging

The HLS-440P Hydrogen Leak Sensor features reduced power consumption, provides increased packaging flexibility, and includes a CAN interface with a standard MQS four-pin connector. Self-testing at start up and advanced error handling ensure reliable operation. In addition, a short-start up time enables an intermittent mode of operation that minimizes current drain.

### Tough and resistant

The HLS-440P Hydrogen Leak Sensor will provide hydrogen detection and measurement for applications where conditions are harsh. With an IP6K9 rating and designed towards Atex Zone 2, this sensor can be installed almost anywhere.

## Key Benefits

- 0-10% H<sub>2</sub>
- Designed for humid environment
- Low cross sensitivity
- Fast response time
- Low power consumption
- Long-term stability and reliability
- Long lifetime

## Applications

- Detection of hydrogen gas leaks in fuel cell systems and other in-process applications

# Hydrogen Leak Sensor

## HLS-440P Specifications

Target gas	Hydrogen
Concentration range	0-10% H <sub>2</sub> in air or nitrogen
Accuracy	± 0.5% typical
Resolution	500 ppm
Speed of response (t90)	< 5 seconds
Speed of recovery	< 5 seconds
Cross-sensitivity	No detection towards HC, H <sub>2</sub> S, N <sub>2</sub> , CO, CO <sub>2</sub> , NOx Humidity influence < 0.5% typical
Start-up time	5 seconds
Self test/Error handling	Developed in accordance to IEC 61508 (SIL2)
Explosion proof	Designed for Atex 100a, Zone 2
Expected lifetime	5 years or 3000 operating hours

### Electrical

Supply voltage	8.5V – 16V
Supply current	70mA typical
Interface	CAN 2.0 ISO 11898
Connector	MQS 4-pin
ESD/Reverse polarity	Yes

### Environmental

Operation temperature range	-40 -> +90° C
Storage temperature range	-50 -> +95° C
Humidity	5-100% R.H including condensation
Pressure	0.5-1.2 bar(a)
EMC	Automotive
Shock	Automotive
Vibration	Automotive

### Mechanical

Dimensions	L = 93.5 mm, Ø = 30 mm
Weight	77g
Material	Stainless steel and PBT +30% GF
Gas filter membrane	Pall SUPOR 450R, 0.45 µm
IP code	IP6K7 and IP6K9K
Process connector	M14x1.5 (ISO-6149-3)

AppliedSensor is not responsible for the design, implementation, manufacture or results from use of products that incorporate AppliedSensor components unless expressly agreed to in writing. Prior to using or distributing any product that incorporates AppliedSensor components, users and distributors should assure adequate design, testing and operating safeguards, and consult with AppliedSensor's technical staff, as necessary. All AppliedSensor components and services are sold subject to AppliedSensor's terms and conditions of sale. For the most current AppliedSensor product information and terms and conditions of sale visit us at [www.appliedsensor.com](http://www.appliedsensor.com). AppliedSensor and the AppliedSensor logo are trademarks of AppliedSensor Sweden AB, AppliedSensor GmbH and AppliedSensor, Inc. Copyright © 2010 AppliedSensor Sweden AB. 04.10

**AppliedSensor Sweden AB**  
Diskettgatan 11  
SE-583 35 Linköping, Sweden  
Tel: +46 13 262 929  
Fax: +46 13 262 929

**AppliedSensor GmbH**  
Gerhard-Kindler-Str. 8  
72770 Reutlingen, Germany  
Tel: +49 7141-51486-0  
Fax: +49-7121-51486-29

**AppliedSensor, Inc.**  
53 Mountain Boulevard  
Warren, NJ 07059, USA  
Tel: +1 908 222-1477  
Fax: +1 (908) 222-1478

**AppliedSensor**  
szss20@163.com  
[www.appliedsensor.com](http://www.appliedsensor.com)

