

Product Specification of:

## O<sub>2</sub> - Scuba Diving Sensor / Type D – 07



### .: KEY FEATURE .:

#### Galvanic gas sensor with an extra water repellent head space and built-in NTC.

*All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa.*

<b>Electrical Connector:</b>	RJ11 modular plug 4P4C
<b>Measurement Range:</b>	0 to 100 Vol.%
<b>Sensor Lifetime:</b>	< 3 years @ ambient air
<b>Expected Operating Life:</b>	~ 500,000 Vol.% h
<b>Response Time t<sub>90</sub>:</b>	< 12 s
<b>Drift:</b>	< 1 % volume O <sub>2</sub> / month @ air, averaged across 12 months
<b>Linearity Error:</b>	< 3 % @ 100 % O <sub>2</sub> , applied for 5 min
<b>Zero Offset Voltage:</b>	< 200 µV in 100 % N <sub>2</sub> , applied for 5 min
<b>Influence of Humidity:</b>	-0.03 % rel. O <sub>2</sub> reading per % RH
<b>Operating Temperature:</b>	0 to 45 °C
<b>Pressure Range:</b>	600 to 1750 hPa
<b>Recommended Load Resistor:</b>	≥ 10 kOhm
<b>Temperature Compensation:</b>	NTC on separated circuit
<b>Interferences:</b>	none to He, H <sub>2</sub> and CO



### .: STORAGE CONDITIONS .:

<b>Temperature Range:</b>	recommended: 5 to 30 °C maximum: -20 to 50 °C
<b>Ambient Pressure:</b>	600 to 1750 hPa
<b>Humidity:</b>	up to 100 % Rh
<b>Shelf Life:</b>	< 6 months recommended
<b>Weight:</b>	approximately 28 g
<b>Material in Contact with Media:</b>	PA, PPS, PTFE, stainless steel

### .: RELATED PRODUCTS .:

Product	Part-No.	Housing Colour
O <sub>2</sub> - Sensor D-07	41 00 57	white

*This data sheet is subject to change without prior notice. [D-07-Rev\_012011.doc]*

page 1 of 1

**IT Dr. Gambert GmbH** .: Hinter dem Chor 21 .: 23966 Wismar .: Germany  
Phone: +49 (0)3841 220 050 .: Fax: +49 (0)3841 220 052 2 .: E-Mail: [sales@itg-wismar.de](mailto:sales@itg-wismar.de)

[www.itg-wismar.de](http://www.itg-wismar.de)