

# Current Detecting Plate Chip Resistor

#### ■ Feature

Model No. "LPZ" is the miniaturized metal plate chip resistors.

High precision has been made possible by using our original trimming method.

It is achieved to have good electrical characteristics by using a special metallic material for the resistor.


Excellent accuracy for current detection, by measure against thermoelectric power. (Applicable for resistance  $\leq 80 \text{m}\,\Omega$ )




### ■ Characteristics

| Item                 | Specification    |                     |  |
|----------------------|------------------|---------------------|--|
| Resistance Range     | 3mΩ ~100mΩ       |                     |  |
|                      | Resistance Range |                     |  |
| Tolerance            | F(±1.0%)         | 3mΩ <b>~</b> 100mΩ  |  |
|                      | $G(\pm 2.0\%)$   | 3mΩ <b>~</b> 9mΩ    |  |
| T.C.R.               | ±100ppm/°C       | 10mΩ <b>~</b> 100mΩ |  |
|                      | ±180ppm/°C       | 5mΩ <b>~</b> 9mΩ    |  |
|                      | ±300ppm/°C       | 3mΩ <b>~</b> 4mΩ    |  |
| Power Rating         | 1W               |                     |  |
| Operating Temp Range | -55°C∼+180°C     |                     |  |
| Rating Ambient Temp. | +70°C            |                     |  |

## **■**Dimensions





## ■ Model Designation

| <u>LPZ</u> | <u>1</u> | R020 | <u>F</u> | E          |
|------------|----------|------|----------|------------|
| 1          | 2        | 3    | 4        | <b>(5)</b> |

|             |              | Symbol            | Meaning             |  |
|-------------|--------------|-------------------|---------------------|--|
| ① Model No. | LPZ          | CURRENT DETECTING |                     |  |
|             |              |                   | PLATE CHIP RESISTOR |  |
| 2           | Power Rating | 1                 | 1W                  |  |
|             |              | R005              | 5mΩ                 |  |
| 3           | Resistance   | ~                 | ~                   |  |
|             |              | R100              | 100mΩ               |  |
| 4           | Tolerance    | F                 | ±1.0%               |  |
|             |              | G                 | ±2.0%               |  |
| 5           | Packaging    | Е                 | Embossed Taping     |  |