

高精度酒精含量检测仪-AT8100

AT8100 酒精含量检测仪主要产品特点：

- 二级报警，报警点可调
- 具有两种单位供用户选择(mg/L， mg/100mL)
- 温度单位切换功能（华氏与摄氏）
- 吹气时间 1-8 秒可调
- 吹气中断提示功能
- 酒精浓度超限提示自动报警
- 点阵液晶屏显示，中文操作界面



AT8100 酒精含量检测仪性能指标及主要技术参数：

- 传感器类型：燃料电池酒精传感器
- 工作电源：2 节 AA 电池
- 相对湿度：=95% (无凝露)
- 测试响应时间：< 20s
- 检测范围：0.000 ~ 1.000 mg/MI
- 报警浓度：0.020%BAC- 0.080%BAC 可调

环境湿度：40%-90%

High precision measuring instrument for measuring alcohol content - AT8100

The AT8100 alcohol tester main features:

, two alarm, alarm point adjustable

Having two units for the user to choose (mg / L, mg / 100mL)

Unit switch function, temperature (Fahrenheit and Celsius)

, 1-8 seconds adjustable blowing time

" Blowing interrupt function

Alcohol concentration exceeded, prompting alarm

, dot matrix LCD display, Chinese operation interface

The AT8100 alcohol content detector performance and main technical parameters:

, sensor types : fuel cell alcohol sensor

" Working power supply: 2 AA batteries

Relative humidity: 95%, (no.)

Response time: < 20s, test

Detection range: 0 ~ 1 mg / ml

Warning: 0.020%BAC - 0.080%BAC concentration, adjustable

The humidity of the environment: 40%-90%

