



基本特性:
 U.L./CSA
 NEMA: 4,7,9,13
 防爆型
 温度 - 34至71°C
 外部设定

6900GZE
 SHIPPING WT.
 APPROX. 19 OZ.
 (539 GRAMS)
 6900GZE-7042
 SHIPPING WT.
 APPROX. 28 OZ.
 (794 GRAMS)

6900GZE

接口尺寸	1/2"
接口材料	不锈钢
隔膜材料	聚丁钠橡胶

最大允许压力 (KG)	可调压力范围 (KG)	压力开关型号	
		SPDT	DPDT
34.48	0.21~1.24	6900GZE12	6900GZEM12
34.48	0.62~4.76	6900GZE14	6900GZEM14
103.45	1.24~9.52	6900GZE16	6900GZEM16
103.45	3.10~23.79	6900GZE18	6900GZEM18
137.93	20.69~63.79	6900GZE20	6900GZEM20
206.90	48.28~160.00	6900GZE22	6900GZEM22

6900GZE-7042

接口尺寸	1/2"
接口材料	不锈钢
隔膜材料	不锈钢

34.48	0.21~1.24	6900GZE12-7042	6900GZEM12-7042
34.48	0.62~4.76	6900GZE14-7042	6900GZEM14-7042
103.45	1.24~9.52	6900GZE16-7042	6900GZEM16-7042
103.45	3.10~23.79	6900GZE18-7042	6900GZEM18-7042
137.93	20.69~63.79	6900GZE20-7042	6900GZEM20-7042
206.90	48.28~160.00	6900GZE22-7042	6900GZEM22-7042

接点容量

电压	电流	
	SPDT	DPDT "M"
	Res.	Res.
125AC~50/60Hz	11	11
250AC~50/60Hz	11	11
30DC	5	5

