

Specification Sheet OXYGEN Nano

Sensor Type O2 Sensor Nano

Detectable Gases O2 Oxygen

Part Number 01-17-30-01

Measuring Principle Amperometric
3-electrode sensor

Specific Sensor Data no

Connector 3 gold contacts with pins



Standard Range 0.0 – 30.0 Vol.%

Lower Detectable Limit (LDL) 0.1 Vol.%

Maximum Range 50 Vol.%

Bias voltage -400 - -600 mV

MAK/TLV

Long Term Sensitivity Drift < 0.1 Vol. % / month

Deviation from linearity at standard range < 5 % FSCurrent at 21 Vol.% Oxygen $7 - 11 \mu A$

Sensitivity ~ 0,04 nA / ppm

Response time at target level

T50 < 5 s

T90 < 15 s

Sensor warm up time typically (pre-sourced) 10 min (10 s)

Operating conditions - 20°C ... +50°C

15 ... 90 % r. h.

Temperature dependence < 0,3 % / °C

Sensor life time 3 years expected

Sensor dimensions 5,5 x 7,7 (+2,8) x 9,8 mm



Specification Sheet Oxygen Nano

Cross Sensitivity

Formula	Test Gas Concentration	Reading in %
NH3	100 ppm	0.0
CO2	5000 ppm	0.0
СО	60 ppm	0.0
Cl2	1.0 ppm	0.0
-	1 %	0.0
H2	100 ppm	0.0
H2S	10 ppm	0.0
СЗН7ОН	1000 ppm	0.0
NO	20 ppm	0.0
NO2	10 ppm	0.0
О3	0.5 ppm	0.0
SO2	20 ppm	0.0
	NH3 CO2 CO Cl2 - H2 H2S C3H7OH NO NO2 O3	Formula Concentration NH3 100 ppm CO2 5000 ppm CO 60 ppm C12 1.0 ppm - 1 % H2 100 ppm H2S 10 ppm C3H7OH 1000 ppm NO 20 ppm NO2 10 ppm O3 0.5 ppm

Please Note: Test conditions at 20°C/ 1013 hPa, Flow Rate > 500 qcm/min Cross sensitivity gases are not target gases. Relation can change with aging.

Solidsense GmbH believes the data contained herein are factual, and the opinions expressed are of qualified experts regarding the results of tests conducted, the data are not to be taken as warranty or representation which Solidsense assumes legal responsibility. The data are offered solely for consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with federal, state, and local laws and regulations. Specifications are subject to change without notice.

Rev. 10-12-07