

# SEMICONDUCTOR GENERAL CATALOG

## Sensors/Image Pickup Devices

Photosensors  
Image Sensors  
Magnetic Sensors

# Photosensors

## Infrared LEDs and Visible LEDs for Sensor Light Sources

Part Number	Part Number with Rank	Package	Electrical/Optical Characteristics (Ta = 25°C)								Applications	
			Radiant Intensity			Radiant Power			Peak Emission Wavelength (nm)	Half-Value Angle (°)		
			Min (mW/sr)	Max (mW/sr)	If (mA)	Min (mW)	Max (mW)	If (mA)				
TLN108(F)	—	TO-18CAN with lens	10	—	50	—	—	—	940	±8	Optoelectronic switches	
TLN105B(F)	—	φ5	12	—	50	—	—	—	950	±23.5	Remote controls	
TLN110(F)	—	φ5	15	—	50	—	—	—	940	±8	Optoelectronic switches	
TLN115A(F)	—	φ5	15	—	50	—	—	—	950	±21	Remote controls	
	TLN115A(B,F)		19	—								
TLN231(F)	—	φ5	35	—	50	—	—	—	870	±16	Fiberless optical transmissions, optoelectronic switches	
TLN233(F)	—	φ5	46	—	50	—	—	—	870	±13		
TLN227(F)	—	φ5	—	—	—	14	—	50	870	±5	Fiberless optical transmissions	
TLN225(F)	—	φ4.9	—	—	—	14	—	50	870	±21		
TLN226(F)	—	φ4.9	—	—	—	14	—	50	870	±13		
TLN119(F)	—	φ3	2.5	10	20	—	—	—	945	±30	Optoelectronic switches	
	TLN119(B,F)		4.2	10								
TLN238(F)	—	φ3	40	—	50	—	—	—	870	±18	Fiberless optical transmissions, optoelectronic switches	
TLN117(F)	—	Small side-view package	2	—	20	—	—	—	940	±15	Optoelectronic switches	
	TLN117(B,F)		2	7.5								
	TLN117(C,F)		5	18.7								
TLOH9204	☆	—	6-pin SMD	15◆	—	20	—	—	612	±4	Specifically designed for digital still cameras	
TLN241	* ☆ ▲	—	1.6(L) x 0.95(W) x 0.6(H) (PCB-mounted)	—	—	—	11	—	30	850	±78/87	Infrared lighting

☆: Dry-packed

◆: Luminous intensity (cd)

▲: Sample available

Note: If = forward current

• Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

\*: New product

## Phototransistors (for Optical Sensors)

Part Number	Part Number with Rank	Package	Electrical/Optical Characteristics (Ta = 25°C)								Applications
			Light Current			Dark Current		Peak Sensitive Wavelength (nm)	Half-Value Angle (°)	Impermeable to Visible Light	
			Min (μA)	Max (μA)	E (mW/cm <sup>2</sup> )	Max (μA)	VCE (V)				
TPS601A(F)	—	TO-18CAN with lens	100	—	0.1	0.2	30	800	±10	—	
	TPS601A(A,F)		100	300							
	TPS601A(B,F)		200	600							
	TPS601A(C,F)		400	1200							
TPS610(F)	—	φ5	100	—	0.1	0.1	24	800	±8	—	
TPS611(F)	—	φ5	30	—	0.1	0.1	24	900	±8	●	
TPS615(F)	—	φ3	20	150	0.1	0.1	24	800	±30	—	
	TPS615(B,F)		34	85							
	TPS615(C,F)		60	150							
	TPS615(BC,F)		34	150							
TPS616(F)	—	φ3	10	75	0.1	0.1	24	900	±30	●	
	TPS616(B,F)		17	42.5							
	TPS616(C,F)		30	75							
	TPS616(BC,F)		17	75							
TPS622(F)	—	Small side-view package	27	—	0.1	0.1	24	870	±15	●	
	TPS622(A,F)		27	80							
	TPS622(B,F)		55	165							

Note: E = radiant incidence; VCE = collector-emitter voltage

• Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

## Photodiodes

Part Number	Package	Electrical/Optical Characteristics (Ta = 25°C)							Applications
		Short-Circuit Current		Dark Current		Peak Sensitive Wavelength (nm)	Half-Value Angle (°)	Impermeable to Visible Light	
		Min (μA)	E (mW/cm <sup>2</sup> )	Max (nA)	V <sub>R</sub> (V)				
TPS703(F)	Side-view package	0.9	0.1	30	10	960	±65	●	Remote controls
TPS704(F)		0.5	0.1	30	10	1000	±65	●	

Note: E = radiant incidence; V<sub>R</sub> = reverse voltage

- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

## Photo-ICs (Analog Output)

Part Number	Package	Electrical/Optical Characteristics (Ta = 25°C)										Applications
		Part Number with Rank	Light Current			Dark Current		Peak Sensitive Wavelength (nm)	Half-Value Angle (°)	Impermeable to Visible Light		
			Min (μA)	Max (μA)	E <sub>v</sub> (lx)	V <sub>CC</sub> (V)	Max (μA)				V <sub>CC</sub> (V)	
TPS820(B,F)	Side-view package	—	1500	6000	E = 0.1 mW/cm <sup>2</sup>	5	0.5	5	870	±15	●	Optoelectronic switches
<i>TPS851(E)</i> ☆	Chip type	—	37	74	100	3	0.17	3.3	600	±55	—	Ambient light sensor
TPS851(E,A)		37	62									
<i>TPS852(T)/TPS852(K)</i> ☆		—	27	54	100	3	0.1	3.3	600	±55	—	
TPS852(A,T)/TPS852(A,K)		30	50									
<i>TPS853(E)</i> ☆		—	37	74	100	3	0.1	3.3	600	±55	—	
TPS853(E,A)		42	70									
<i>TPS856(T)/TPS856(K)</i> ☆		—	40	80	100	3	0.1	3	550	±55	—	
TPS856(A,T)/TPS856(A,K)		44.1	73.7									
<i>TPS859(T)/TPS859(K)</i> ☆	—	160	320	100	3	0.2	3	550	±55	—		
TPS859(A,T)/TPS859(A,K)	180	300										

☆: Dry-packed

Note 1: V<sub>CC</sub> = power supply voltage; E<sub>v</sub>: Illuminance; E = radiant incidence

Note 2: (T) = For world wide except japan, (K) = For japan

- The products shown in italic are manufactured by Toshiba semiconductor (Thailand) Co.,Ltd.
- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

## Photointerrupters (Phototransistor Output)

Part Number	Part Number with Rank	Package	Gap (mm)	Slit Width (mm)	Electrical Characteristics (Ta = 25°C)				Absolute Maximum Ratings (Ta = 25°C)	Applications
					Current Transfer Ratio				Collector-Emitter Voltage (V)	
					Min (%)	Max (%)	If (mA)	VCE (V)		
TLP832(F)	—	PWB direct mounting	5	0.5	5	100	10	2	35	Printers, fax machines, copiers, image scanners, vending machines
TLP833(F)	—		5	0.5	5	100	10	2	35	
TLP831(F)	—		4.2	0.5 (Note 1)	5	100	10	2	35	
TLP830(F)	—		2	0.15	3	20	10	2	35	
TLP848(E)	☆	Surface-mount, ultra-compact package	1.2	0.3	3	24	5	2	15	Cameras, cellular phones
	TLP848(R)		1.2	0.3	4	20	5	2	15	

☆: Dry-packed

Note: PWB = printed wiring board; If = forward current; VCE = collector-emitter voltage

Note 1: Horizontal slit

- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

## Photointerrupters (with Connector)

Part Number	Package	Gap (mm)	Slit Width (mm)	Electrical Characteristics (Ta = 25°C)			Connector Manufacturer	Applications
				Operating Supply Voltage (V)	Output Type			
					With Resistor	Open-Collector		
TLP1243(C8)	Snap-in mounting	5	0.7	VCE ≤ 35 V	—	Phototransistor output	Tyco Electronics AMP K.K.	Printers, copiers, fax machines, vending machines, FA equipment, amusement equipment

Note: VCE: collector-emitter voltage

- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

# Image Sensors

## CCD Linear Image Sensors

Part Number	Style	Photosensitive Pixels (Picture Elements)			Sensitivity (Typ.) (V/lx · s)	Data Rate (Max) (MHz)	Other Features
		Type/Lamp	Effective Pixels	Size (µm)			
<b>TCD1103GFG</b> ☆	Lens reduction type	B/W	1500	5.5 x 64	79	2	Digital shutter Sample-and-hold
<b>TCD1254GFG</b> ☆			2500	5.25 x 64	103	2	
TCD1706DG			7400	4.7 x 4.7	15	25 x 4	
TCD1710DG			7500 x 2 Line		15	15 x 2	
TCD1711DG			7450		15	30 x 2	
TCD2563BFG		5340 x 4 Line	5.25 x 8.4	R:22.6, G:28.0, B:17.0		Color:25, B/W:25 x 2	TDI
TCD2564DG		5400 x 3 Line	7 x 7	R:9.6, G:8.9, B:3.8		30 x 2	
TCD2565BFG		7500 x 4 Line	5.25 x 5.25	R:10.2, G:9.2, B:4.0, B/W:14.7		Color:35, B/W:35 x 2	2-line distance (color)
TCD2709DG		7450 x 3 Line	4.7 x 4.7	R:5.7, G:5.2, B:2.2		25 x 2	
TCD2710DG		7500 x 3 Line	9.325 x 9.325	R:9.3, G:14.5, B:4.8		30 x 2	
TCD2712DG		7500 x 3 Line	9.325 x 9.325	R:14.1, G:22.2, B:9.1		30 x 4	
TCD2713DG		7500 x 4 Line	9.325 x 9.325	R:13.1, G:18.4, B:7.6, B/W:23.8		Color:35 x 2, B/W:35 x 4	2-line distance (color)
TCD2715DG		7450 x 3 Line	4.7 x 4.7	R:5.7, G:5.2, B:2.2		30	
TCD2716DG		7450 x 3 Line	4.7 x 4.7	R:9.1, G:8.5, B:3.8		30 x 2	
TCD2717BFG		7500 x 4 Line	4.7 x 4.7	R:8.0, G:7.2, B:3.1		Color:35, B/W:35 x 2	2-line distance (color)
TCD2915BFG		10680 x 3 Line	2.625 x 8.4	R:5.6, G:7.0, B:4.3		20	
TCD2916BFG		10680 x 4 Line		R:6.7, G:7.0, B:4.3, B/W-H:17.4, B/W-H:11.3		Color:25, B/W:25 x 2	
TCD2964BFG		21360 x 6 Line	2 x 4	R:1.3, G:1.5, B:0.7		10	Overflow drain

☆: Dry-packed

\*: New product

- The products shown in bold are also manufactured in offshore fabs.
- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

## Area Image Sensors (Dynastron™)

Part Number	Package	Features			
		Optical Format (Inches)	Total Pixel Count (PIX)	Color/Mono	Digital Signal Processor
TCM9001MD	Camera module	1/10	648 (H) x 492 (V) (VGA)	Color (RGB)	Yes
TCM9200MD	Camera module	1/4	1648 (H) x 1216 (V) (2.0M)	Color (RGB)	Yes

- Dynastron is a trademark of Toshiba Corporation.
- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

Package	Resolution (DPI)	Applications	Remarks	
16PIN GLCC	—	Barcode readers		
22PIN Cerdip	A3 600	Photocopiers, scanners		
22PIN CLCC	A4 600	Photocopiers, color scanners		
22PIN Cerdip				
22PIN CLCC	ES: OK			
22PIN Cerdip				
68PIN Cerdip	A3 600			
22PIN Cerdip				
32PIN CLCC				
22PIN CLCC	A4 1200			
32PIN CLCC	A4 4800		Color scanners	

# Magnetic Sensors

## Magnetic Sensors (Digital Output)

Part Number	Pole	Output	Supply Voltage V <sub>CC</sub> (V)			Supply Current @ V <sub>CC</sub> = 2.3 to 2.7 V						Magnetic Flux Density						Operating Frequency (Hz)			Package
						Average Current I <sub>CC</sub> (μA)			Operating Current I <sub>CCON</sub> (mA)			Operating Point B <sub>ON</sub> (mT)			Releasing Point B <sub>OFF</sub> (mT)						
			min	typ.	max	min	typ.	max	min	typ.	max	min	typ.	max	min	typ.	max	min	typ.	max	
TCS10SPU	S	Push-pull	2.3	—	3.6	—	5.5	9.5	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS10SLU		Open-drain	2.3	—	3.6	—	5.5	9.5	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS11SLU		Open-drain with inverting output	2.3	—	3.6	—	5.5	9.5	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS10NPU	N	Push-pull	2.3	—	3.6	—	5.5	9.5	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS10NLU		Open-drain	2.3	—	3.6	—	5.5	9.5	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS11NLU		Open-drain with inverting output	2.3	—	3.6	—	5.5	9.5	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS10DPU	S/N	Push-pull	2.3	—	3.6	—	8.5	13.2	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS10DLU		Open-drain	2.3	—	3.6	—	8.5	13.2	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS11DLU		Open-drain with inverting output	2.3	—	3.6	—	8.5	13.2	—	0.7	1.3	—	1.8	2.5	0.3	0.8	—	—	25	—	
TCS20DPR		Push-pull	2.3	—	3.6	—	★7.3	★13.2	—	★0.7	★1.1	—	3.4	4.4	0.9	2.0	—	—	25	—	
TCS20DLR	Open-drain	2.3	—	3.6	—	★7.3	★13.2	—	★0.7	★1.1	—	3.4	4.4	0.9	2.0	—	—	25	—		

Note: The UFV package measures 2.0 × 2.1 × 0.7 mm and is a variant of SC-88A.

The SOT-23F package measures 2.9 × 2.4 × 0.8 mm (Similar package as SOT-23).

★: When V<sub>CC</sub> = 2.3 V

- Contact the Toshiba sales representative for information about RoHS compliance before you purchase any components.

SUNSTAR 商斯达实业集团是集研发、生产、工程、销售、代理经销、技术咨询、信息服务等为一体的高科技企业，是专业高科技电子产品生产厂家，是具有10多年历史的专业电子元器件供应商，是中国最早和最大的仓储式连锁规模经营大型综合电子零部件代理分销商之一，是一家专业代理和分销世界各大品牌IC芯片和电子元器件的连锁经营综合性国际公司，专业经营进口、国产名厂名牌电子元件，型号、种类齐全。在香港、北京、深圳、上海、西安、成都等全国主要电子市场设有直属分公司和产品展示展销窗口门市部专卖店及代理分销商，已在全国范围内建成强大统一的供货和代理分销网络。我们专业代理经销、开发生产电子元器件、集成电路、传感器、微波光电元器件、工控机/DOC/DOM 电子盘、专用电路、单片机开发、MCU/DSP/ARM/FPGA 软件硬件、二极管、三极管、模块等，是您可靠的一站式现货配套供应商、方案提供商、部件功能模块开发配套商。商斯达实业公司拥有庞大的资料库，有数位毕业于著名高校——有中国电子工业摇篮之称的西安电子科技大学（西军电）并长期从事国防尖端科技研究的高级工程师为您精挑细选、量身订做各种高科技电子元器件，并解决各种技术问题。

微波光电部专业研制、代理经销高频、微波、光纤、光电元器件、组件、部件、模块、整机；电磁兼容元器件、材料、设备；微波CAD、EDA 软件、开发测试仿真工具；微波、光纤仪器仪表。欢迎国外高科技微波、光纤厂商将优秀产品介绍到中国、共同开拓市场。长期大量现货专业批发高频、微波、卫星、光纤、电视、CATV 器件：晶振、VCO、连接器、PIN 开关、变容二极管、开关二极管、低噪晶体管、功率电阻及电容、放大器、功率管、MMIC、混频器、耦合器、功分器、振荡器、合成器、衰减器、滤波器、隔离器、环行器、移相器、调制解调器；光电子元件和组件：红外发射管、红外接收管、光电开关、光敏管、发光二极管和发光二极管组件、半导体激光二极管和激光器组件、光电探测器和光接收组件、光发射接收模块、光纤激光器和光放大器、光调制器、光开关、DWDM 用光发射和接收器件、用户接入系统光收发器件与模块、光纤连接器、光纤跳线/尾纤、光衰减器、光纤适配器、光隔离器、光耦合器、光环行器、光复用器/转换器；无线收发芯片和模组、蓝牙芯片和模组。

更多产品请看本公司产品专用销售网站：[欢迎索取免费详细资料、设计指南和光盘；产品凡多，未能尽录，欢迎来电查询](#)

商斯达中国传感器科技信息网：<http://www.sensor-ic.com/>

商斯达工控安防网：<http://www.pc-ps.net/>

商斯达电子元器件网：<http://www.sunstare.com/>

商斯达微波光电产品网：[HTTP://www.rfoe.net/](http://www.rfoe.net/)

商斯达消费电子产品网：<http://www.icasic.com/>

商斯达实业科技产品网：<http://www.sunstars.cn/> 微波元器件销售热线：

地址：深圳市福田区福华路福庆街鸿图大厦1602 室

电话：0755-82884100 83397033 83396822 83398585

传真：0755-83376182 (0) 13823648918 MSN: SUNS8888@hotmail.com

邮编：518033 E-mail:szss20@163.com QQ: 195847376

深圳赛格展销部：深圳华强北路赛格电子市场2583 号 电话：0755-83665529

技术支持: 0755-83394033 13501568376