


Flexco Microwave, Inc.

PO Box 115, 17 Karrville Road
Port Murray, NJ 07865
Telephone 908-835-1720
Fax 908-835-0002
E-mail sales@flexcoMW.com
http://www.FlexcoMW.com



FC392 Flexible Coaxial Cable
18 GHz Cable

Frequency vs. Attenuation




Electrical Characteristics:

- Nominal Impedance: 50Ω
- Velocity of Propagation: 88.5%
- Effective Dielectric Constant: 1.28
- Time Delay: 1.15 ns/ft
- Shielding Effectiveness: -90 dBc min.
- Dielectric Withstanding Voltage: 3.0 KV (@ 60 Hz, Sea Level/25°C)
- Nominal Capacitance: 25 pF/ft
- Maximum VSWR:
 - Precision Straight connectors:
 - DC - <4 GHz 1.10:1
 - 4 GHz - <8 GHz 1.15:1
 - 8 GHz - 18 GHz 1.25:1
 - Non-Precision or Angle connectors:
 - DC - <4 GHz 1.20:1
 - 4 GHz - <8 GHz 1.30:1
 - 8 GHz - 18 GHz 1.40:1
- Maximum Frequency: 18 GHz

For phase and other electrical characteristics, please consult the appropriate section of catalog.

Frequency (GHz)	Maximum Insertion Loss (dB/ft)	Typical Insertion Loss (dB/ft)	Precision Connector Loss (dB)	Non Precision Connector Loss (dB)
0.04	0.008	0.006	0.01	0.02
0.10	0.016	0.014	0.02	0.03
0.30	0.021	0.018	0.02	0.03
0.50	0.035	0.032	0.02	0.03
1.0	0.055	0.048	0.02	0.03
2.0	0.075	0.064	0.03	0.05
3.0	0.095	0.082	0.04	0.06
4.0	0.110	0.096	0.04	0.06
5.0	0.125	0.109	0.05	0.08
6.0	0.135	0.120	0.06	0.09
7.0	0.150	0.133	0.06	0.09
8.0	0.160	0.143	0.07	0.11
9.0	0.170	0.154	0.07	0.11
10.0	0.180	0.162	0.08	0.12
11.0	0.190	0.170	0.08	0.12
12.0	0.200	0.183	0.08	0.12
13.0	0.210	0.188	0.09	0.14
14.0	0.220	0.198	0.09	0.14
15.0	0.225	0.204	0.10	0.15
16.0	0.235	0.212	0.10	0.15
17.0	0.245	0.220	0.11	0.17
18.0	0.250	0.230	0.11	0.17



Physical Characteristics:

- Center Conductor: Solid SPC per ASTM-B298
- Dielectric: PTFE per L-P-403
- Outer Conductor: Strip wound oxygen free 0.375" max. O.D.
- Minimum Internal Bend Radius: 1.5 inches
- Operating Temperature: -60°C to +175°C
- Weight per Foot (unjacketed): 0.107 lbs
- Connector Interface: Per MIL-C-39012

Optional Jacketing and Braid:

- Polyolefin per MIL-I-23053/5: 0.420" max. O.D.
- Neoprene per MIL-I-23053/1: 0.450" max. O.D.
- FEP per MIL-I-23053/11: 0.405" max. O.D.
- Braid: Bronze per UNS C22000, 0.420" max. O.D.
- Others available, please consult factory.