

IT

**International Technologies
Dr. Gambert GmbH**

Product Specification of:

O₂ - Medical Sensor:

Type: M-10

Part. No.: 41 00 14

Key Features: Gas sensors that shows high signal stability at low cross interferences to anesthesia gases combined with superior linearity over the entire range

All characteristics are based on conditions at 25°C, 50% rel. H. and 1013 mBar

Electrical Connector:	modular jack 6P4C
Measurement Range:	0 to 100 Vol.%
Nominal Sensor Life:	more than 500 000 Vol.% h
Expected Operating Life:	less than 3 years @ ambient air
Output Signal:	8.0 to 12 mV @ dry ambient air
Response Time t_{90} :	less than 12 sec
Drift:	less than 1% volume O ₂ / month @ air
Operating Temperature:	0 to 40°C
Pressure Range:	600 to 1750 hPa
Linearity Error:	less than 3% @ 100% O ₂ applied for 5 min
Zero Offset Voltage:	less than 200 μ V in 100% N ₂ , applied for 5 min
Repeatability:	\pm 1% volume O ₂ @ 100% O ₂ , applied for 5 min
Influence of Humidity:	-0.03% rel. O ₂ reading per % r.H.
Recommended Load Resistor:	more than 10 kOhm
Temperature Compensation:	NTC
Interferences:	< 0.5 % O ₂ response to: 10.0 % CO ₂ balance N ₂ 80.0 % N ₂ O balance N ₂ 7.5 % Halothane balance N ₂ 7.5 % Isoflurane balance N ₂ 7.5 % Enflurane balance N ₂ 7.5 % Sevoflurane balance N ₂ 20.0 % Desflurane balance N ₂

Storage Conditions

Temperature Range:	recommended: 5 to 30°C maximum: - 20 to 50°C
Ambient Pressure:	600 to 1750 hPa
Humidity:	up to 100% rel. H.
Shelf Life:	less than 6 months
Weight:	approximately 52 g
Material in contact with media:	PA, PPS, PTFE, stainless steel
Warranty Period:	16 months
Colour:	black housing

[M-10 Rev09-02.doc]

page 1/2

IT Dr. Gambert GmbH, Hinter dem Chor 21, 23966 Wismar, Germany

Tel.: +49 (0) 3841 22 00 50, Fax: +49 (0) 3841 22 00 522, sales@IT-Wismar.de, www.IT-Wismar.de



O₂ - Medical Sensor:

Type: M-10

Part. No.: 41 00 14

Outline Dimensions and Pin Configuration

(Dimension units are: mm)

