

Quartz

Type 9726A...

Impulse Force Hammer; High Force Range


Dynamic quartz sensor elements contained within instrumented hammers are used to deliver a measurable force impulse (amplitude and frequency content) to excite a mechanical structure under test. A response signal measured with an accelerometer in conjunction with a FFT analyzer provides the transfer function of the structure.

- Low impedance, voltage mode
- Quartz sensing element guarantees long-term stability
- Accessories for various applications
- Sensor cable integrated to hammer handle
- Conforming to CE



Description

The dynamic response of a mechanical structure while either in a development phase or an actual use environment can readily be determined by impulse force testing. Using a FFT analyzer, the transfer function of the structure can be determined from a force pulse generated by the impact of a hammer and the response signal measured with an accelerometer. The impulse force test method, yields extensive information about the frequency and attenuation behavior of the system under test.



The stainless steel head of an impulse force hammer, is equipped with a quartz, low impedance force sensor which accepts impact tips varying in hardness. A selection of steel, plastic, PVC and rubber tips along with an extender mass allow the hammer to be tailored to impart to the test structure, a desired spectrum of frequencies. Shear quartz accelerometers operating in a voltage mode and featuring insensitivity to base strain, thermal transients and transverse motion are available to measure the response of the test specimens ranging from thin-walled structures to steel bridge members.

Application

The hammer may be used for testing medium to heavy structures such as large rotating machinery and truck gear assemblies and structural members at low to medium frequencies. The impulse force hammer is used to analyze the dynamic behavior of mechanical structures. The vibrations induced by the hammer impact are measured by an accelerometer.

The hammer incorporates a quartz measuring cell with built-in Piezotron® low impedance electronics. The cell's voltage mode operation, guarantees a stable signal transmission insensitive to ambient influences. A wide selection of single or multi-channel couplers are available to provide power and signal processing for the hammer and accelerometers.

9726A_000-274e-05.05

Technical Data

Type	Units	9726A5000	9726A20000
Force Range	N	0 ... 5000	0 ... 20000
Maximum Force	N	10000	25000
Sensitivity nom.	mV/N	1	0,2
Resonant Frequency	kHz	27	27
Frequency range with steel impact tip (-10 dB)	Hz	5000	5400
Time Constant nom.	s	500	500
Rigidity	kN/μm	0,8	0,8
Temperature Range Operating	°C	-20 ... 70	-20 ... 70
Output:			
Voltage FSO	V	±5	±5
Bias nom.	VDC	11	11
Impedance	Ω	<100	<100
Source:			
Voltage	V	20 ... 30	20 ... 30
Constant current	mA	2 ... 20	2 ... 20
Hammer head dimensions:			
Diameter	mm	32	32
Length	mm	94	94
Weight	grams	500	500
Length of handle	mm	236	236
Connector	type	BNC neg.	BNC neg.

1 N = 0,2248lb, 1 g = 9,80665 m/s², 1 inch = 25,4 mm, 1 gram = 0,03527 oz

Accessories Included

- | | Type |
|-------------------------------------|-------|
| • impact tip, steel | 9902A |
| • impact tip, steel with Delrin cap | 9904A |
| • impact tip, soft PVC | 9906 |
| • impact tip, rubber hard (green) | 9908 |
| • impact tip, rubber medium (red) | 9910 |
| • impact tip, rubber soft (gray) | 9912 |
| • adapter for rubber impact tips | 9928 |
| • extender mass (250 grams) | 9926 |
| • impact tip wrench | 1370 |
| • Plastic carrying case | |

Ordering Key

Measuring Range

5000 N	5000
20000 N	20000

9726A

9726A_000-274e-05.05